

IB930

Socket 479 Intel® Core™ 2 Duo Half Size PISA CPU Card



(click to zoom)
[Datasheet in PDF](#)



FEATURES

- Supports Intel® **Core™ 2 Duo** /Core™ Duo/Solo
- Supports up to 2.33GHz, 533MHz/667MHz FSB
- One DDR2 DIMM with 2GB capacity
- Integrated VGA with shared memory. Supports CRT/LVDS
- Marvell PCI-Express Gigabit LAN
- Watchdog timer, Digital I/O, PCI to ISA bridge
- Type 2 CF socket on board, Mini PCI slot
- 2x SATA, 5x USB (2.0) ports support, 4x serial ports

IB930 SPECIFICATIONS

CPU Socket

Socket 479

CPU

Supports Intel® **Core™ 2 Duo** /Core™ Duo /Solo processors

Up to 2.33GHz

CPU Front Side Bus (FSB)

533Hz / 667MHz

Chipset

Intel® 945GM chipset

ICH7M

BIOS

Award BIOS, ACPI supported

System Memory

One DDR2 socket supports up to 2GB DDR SDRAM
PC400/533/667 DDR SDRAM

Integrated VGA

Intel® 945GM integrated VGA for CRT

Supports DVMT 3.0 for memory allocation

LVDS

Chrontel CH7308B on board supports 18 or 24-bit single/dual channel LVDS

LAN

Marvell 88E8053 PCI Express Gigabit LAN controller

RJ-45 connector on bracket

Audio

ICH7M Built-in Audio controller + AC97 Codec

ALC655 w/ 6 channels (Line-out, Line-in, Mic.)

Multi I/O

ICH7M, Winbond W83627EHF, Fintek F81216

Supports 1x IDE, 2x SATA, **4x COM** (COM2 (RS232/RS422/RS485), 1x FDD, 1x KB, 1x Mouse

IDE Interface

Built in ICH7M; One enhanced IDE channel supports

Serial ATA

ICH7M built-in SATA controller,

supports 2 ports

USB (2.0)

ICH7M built-in USB 2.0 host controller, support 5 ports

IrDA

Pin header

Keyboard and Mouse Connector

PS/2 type

Watchdog Timer

Generates system reset; 256 levels

Hardware Monitoring

Built in W83627EHF; monitors system/CPU temperature and voltage status

Digital I/O

4 in / 4 out

PCI to ISA

ITE8888G FTBGA (no ISA master)

Expansion Slot

Mini PCI socket

Edge Connectors (on bracket)

PS/2 for keyboard/mouse, USB, VGA CRT, RJ-45 SPDIF, four USB, RCA, S-Video, COM1

Onboard Connectors/Headers

IDE1, CF socket, parallel port, COM1, USB x 4, LVDS, audio, slim FDD, IrDA, 2x SATA, Digital I/O

Form Factor

Half Size CPU Card

Dimensions

2 IDE devices; supports UDMA33/66/100
Supports CF socket

FDD Interface

Onboard slim FDD connector

Serial Ports

Four serial ports ports

186mm by 129mm

Environmental Factors:

Operating Temperature:

0°C~60°C (32°F~140°F)

Storage Temperature:

-20°C~80°C (-68°F~176°F)

Relative Humidity:

10%~90% (non-condensing)

Ordering Information:

IB930-R - Socket 479 Intel® 945GM **Core™ 2 Duo** Core Half size PISA CPU card with VGA, Gigabit LAN, 4x COM, CF, Mini PCI

PACKING LIST:

1 x Driver CD

1 x User's Manual

1 x Serial port

1 x Serial ATA

1 x IDE Ribbon Cable (40-pin)

1 x Audio cable

1 x PS2 keyboard/mouse cable