


ET910

Intel® Core™ 2 Duo ETX CPU Module with Intel® 945GM Chipset



[Click to enlarge](#)
[Datasheet in PDF](#)

FEATURES

- Socket 478 for Intel® Core™ 2 Duo /Core™ Duo/Solo
- Up to 1.86GHz CPU speed, 533MHz/667MHz FSB
- Integrated ICH7M VGA supports CRT, dual channel LVDS
- Integrated ICH7M 10/100 BaseT Ethernet
- USB 2.0 x4, SATA x2, IDE, AC97, Watchdog timer
- 95mm x 114mm

ET910 SPECIFICATIONS

CPU

Supports Intel® Core™ 2 Duo /Core™ Duo /Solo processors

Up to 1.86GHz

CPU Front Side Bus (FSB)

533Hz / 667MHz

Chipset

Intel® 945GM chipset

ICH7M

BIOS

Award BIOS, ACPI supported

System Memory

One DDR2 SODIMM socket, Max. 2GB capacity

Integrated VGA

Intel® 945GM integrated VGA for CRT/TV out

Supports DVMT 3.0 for memory allocation

LVDS

Intel® 945GM integrated for 18-bit dual channel

LVDS

LAN

ICH7M integrated 10/100 BaseT Ethernet

Audio

ICH7M integrated audio with AC97 codec

Multi I/O

ICH7M, supports 1x IDE, 2x SATA, 2x COM

IDE Interface

Built in ICH7M; One enhanced IDE channel supports 2 IDE devices including HDD, CF or DOM on carrier board; supports UDMA33/66/100

USB

Up to 4 USB ports (USB 2.0, to be supported by the baseboard)

SATA

Up to 2 SATA ports

Other Features

Watchdog timer, IrDA

Connector to Carrier Board

Hirose FX8-100P-SV ETX connector x4

for PCI bus, USB, audio, VGA/CRT, LVDS, LAN, COM ports, parallel port, IDE, PS/2 keyboard/mouse and ISA bus

Power

+5V, 5VSB & 3V for RTC

Dimensions

95mm x 114mm

Environmental Factors:

Operating Temperature

0°C~60°C (32°F~140°F)

Storage Temperature

-20°C~80°C (-68°F~176°F)

Relative Humidity

10%~90% (non-condensing)

Ordering Information:

ET910- Intel® Core™ 2 Duo ETX CPU Module with Intel® 945GM Chipset (Socket based)

ET910-1600- Intel® Core™ Duo ETX CPU Module with Intel® 945GM Chipset (CPU: L2400 LV, 1.66GHz, 667FSB, 2MB L2)

ET910-1500- Intel® Core™ 2 Duo ETX CPU Module with Intel® 945GM Chipset (CPU: L7400 LV, 1.56GHz, 667FSB, 4MB L2)